



ST600V

AUTOMATIC SKINNING MACHINE - LONG MODEL

MODEL



TECHNICAL DATA

FEATURE	DATA
Operators	1-2
Voltage range (1)	220- 480V 50-60Hz
Power (1)	2,25kW/3 ph
Controls	24V
LxWxH (2)	2827 x 660 x 1467mm
Weight (3)	315 kg
Working width (2)	455 mm
Water usage	8 l/m
Water connection	1/2"
Air usage	-
Air connection	-
Speed (4)	+/- 17 m per minute

(1) depending on requested voltage

(2) 1mm = 0,03937 inches

(3) 1kg = 2,20462 pounds

(4) $\left(\frac{1700 \text{ cm/min}}{\text{length fillet (cm)} + 5 \text{ cm}} \right) \times 2 = \text{theoretical capacity}$

DESCRIPTION



Versatile automatic skinning machine suitable for many fish species and sizes. Please check our website and product matrix on the main folder for more information. When ordering, please provide STEEN with the electrical specifications and water connection available. Also inform us which fish species (preferably the scientific name) you would like to process including capacity and general length. Please also indicate if you have any special requirements regarding the product.




Универсальная автоматическая машина для снятия кожи с различных видов рыбы разного размера. Для получения дополнительной информации, пожалуйста, посетите наш веб-сайт и посмотрите таблицу продуктов в основной папке. При заказе, пожалуйста сообщите STEEN о требуемых характеристиках электропитания и подсоединения воды. Также сообщите нам, какие виды рыбы (желательно научное название) вы хотели бы обрабатывать, планируемые объемы переработки, длину рыбы. Также укажите, есть ли у вас какие-либо особые требования к продукту.



多功能自动去皮机适合于很多类型和尺寸的鱼，请查阅我们网站和产品列表以获得更多信息，订货时，请向STEEN公司说明电器规范和水源连接规格，还有告诉我们您加工的是哪种鱼（最好是学名），以及产量和一般长度，请说明您对于鱼是否有特殊的要求。



FOOTPRINT



Due to the high degree of customization possibilities, technical data of the final product may vary.



OPTIONS



ST600V

AUTOMATIC SKINNING MACHINE - LONG MODEL



600/100E

1



Table in front of infeed conveyor with water for faster feeding

600/GUIDE


2



Fish guiding system

600/RAZOR

3



Different knife sizes for optimal result

600/INFEED

4



Short infeed conveyor = -454mm

600/OUTFEED


5



Short outfeed conveyor = -619mm

CUSTOMIZED

6



Tailor-made solution

Due to the high degree of customization possibilities, technical data of the final product may vary.